



Black Bearing

			C (crankset diameter)					
			B (frame width)	24 & GXP (adaptor)	25 (campagnolo)	DUB (29 mm)	30	Praxis (30/28)
A (frame diameter)	to screw	BSA / BSC (dia 34)	68 / 73	BSA-68/73-24...  	BSA-68/73-25...  	BSA-68/73-D...  	BSA-68/73-30...  	BSA-68/73-P...  
		T47 (dia 47)	68 / 73	T47-68/73-24...  	T47-68/73-25...  	T47-68/73-D...  	T47-68/73-30...  	T47-68/73-P...  
			77	T47A-24...  		T47A-D...  	T47A-30...  	T47A-P...  
			86 / 92	T47-86/92-24...  	T47-86/92-25...  	T47-86/92-D...  	T47-86/92-30...  	T47-86/92-P...  
		ITA (dia 36)	68 / 73	ITA-70-24...  	ITA-70-25...  	ITA-70-D...  	ITA-70-30...  	ITA-70-P...  
	to press	41	86 / 92	41-86/92-24...   	41-86/92-25...   	41-86/92-D... 	41-86/92-30... 	41-86/92-P... 
		42	68 / 73	42-68/73-24...   	42-68/73-25...   	42-68/73-D...   	42-68/73-30...   	42-68/73-P...   
		46	68 / 73	46-68/73-24...   	46-68/73-25...   	46-68/73-D...   	46-68/73-30...   	46-68/73-P...   
			73A	46-73A-24...   	46-73A-25...   	46-73A-D...   	46-73A-30...   	46-73A-P...   
			79	46-79-24...  	46-79-25...   	46-79-D...   	46-79-30...   	46-79-P...   
			68 / 92	46-68/86-24...   	46-86/92-25...   	46-68/92-D...   	46-68/92-30...   	46-68/92-30...   
		65	63	65-63-24...   		65-63-D...   	65-63-30...   	65-63-P...   



aluminium cup

interchangeable bearing

bb lock technology

deliver without tool : standart shimano hollotech

deliver with Blackbearing tool

No tool -bottom bracket to press